# User Manual of Bluetooth control box

### **Included Parts**

- 1 Bluetooth RGB LED Waterproof Controller
- 8 22-18 AWG Butt Crimp Connectors
- 4 M4 Bolts
- 4 M4 Washers
- 4 M4 Nuts

### **Specifications**

### WK-BC controller

Input Voltage

12~24 VDC

Output **Total Output**  6 Amps/ Ch

360 Watts @12 VDC

Max Wattage

360W (12V) / 720W (24V)

Operating Temperature

-20~110°F (-30~45 °C)

Dimmable

IP Rating Standards and Certifications Weatherproof IP68

SELECTOR

CE / RoHS


Warranty

2 Years



### **Download Instructions**

1. Download application by either scanning the QR code or by searching for LED BLE.



3. DO NOT connect bluetooth controller within device's bluetooth settings.

### **QR** Code



## **Application Connection and Operation**

DYNAMIC MODE SELECTION

CUSTOM COLOR DYNAMIC MODES



# To Power Supply (Match voltage to LED voltage) 2.Outputs - Use one or both for your application RGB Light

### Safety

- DO NOT connect controller or LEDs directly to 120V AC power. This controller requires a 12Vor 24V DC power supply.
- DO NOT exceed max load of 18 Amps, overloading the controller may cause overheating, shorting, and possibly failure of controller.
- Be sure the power supply is not plugged into an outlet before connecting or disconnecting any of the systems components.
- DO NOT expose the controller or remote strip to direct or indirect moisture.
- Always observe proper polarity when connecting power and load.

### **Dimensional Diagram**

