




44W
 UGR<19

 95
 lm/W

 DIMMABLE
 PUSH



Recessed LED Panel - 120X30cm - PUSH Dimmable - 44W - UGR19

Ref. K5236-PUSH

Ultra-thin recessed LED panel with cutting-edge technology that enables it to provide powerful and even illumination. It's a high efficiency luminaire with a power of 44W and a luminous flux of 2900 lumens. It incorporates a PUSH dimming driver, providing the possibility to adjust the light intensity. Thanks to its low glare index, UGR19, this panel provides great visual comfort. It's available in three color temperatures: warm white (3000K), neutral white (4000K) and cool white (6000K).



Product data

Hue	Cool white, Neutral white, Warm white
Kelvin (K)	3000, 6000, 4000
Lumens (Lm)	2900
CRI	80-85
LED Type	SMD 2835
Dimmable	Yes
Power (W)	44
Nominal Voltage (V)	220 - 240 V/AC
Frequency (Hz)	50 - 60
Orientable	No
Diffuser material	Polycarbonate
Use Outdoor	No
IP	IP20
Frequency of use	Intensive
Lifetime (h)	25000
Certificates	CE, ROHS
Warranty	According to legal guarantee: 2 years
Cutting dimensions (mm)	1200x300



Mounting	Recessed
LED Panel dimensions	120x30

Product variants

Reference

Attributes

K5236-PUSH-BC

Colour temperature - Warm White



K5236-PUSH-BN

Colour temperature - Neutral White



K5236-PUSH-BF

Colour temperature - Cool White

