



Recessed LED panel - 120X60cm - 0-10V dimmable - 72W - UGR19

Ref. K5234-0-10

Ultra-thin recessed LED panel with cutting-edge technology that enables it to provide powerful and even illumination. It's a high efficiency luminaire with a power of 72W and a luminous flux of 5900 lumens. It incorporates two 0-10V dimming drivers, providing the possibility to adjust the light intensity. Thanks to its low glare index, UGR19, this panel provides great visual comfort. It's available in three color temperatures: warm white (3000K), neutral white (4000K) and cool white (6000K).





Product data

Hue	Cool white, Neutral white, Warm white
Kelvin (K)	3000, 6000, 4000
Lumens (Lm)	5900
Efficiency (Lm/w)	85
CRI	80-85
Beam angle (°)	120
UGR	UGR19
LED Type	SMD 2835
Dimmable	Yes
Power (W)	72
Nominal Voltage (V)	220 - 240 V/AC
Frequency (Hz)	50 - 60
Sensor	No
Orientable	No
Dimensions (mm) LxIxh	1200 x 600 x 6
Diffuser material	Polycarbonate
Use Outdoor	No
IP	IP20



Temperature range	-18°C ~ +55°C
Frequency of use	Intensive
Lifetime (h)	25000
Certificates	CE, ROHS
Warranty	According to legal guarantee: 2 years
Cutting dimensions (mm)	1200x600
Mounting	Recessed
LED Panel dimensions	120x60

Product variants

Reference	Attributes	
K5234-0-10-BC	Colour temperature - Warm White	
K5234-0-10-BN	Colour temperature - Neutral White	
K5234-0-10-BF	Colour temperature - Cool White	