





## Recessed circular LED downlight 6W -Cut Ø 110 mm-5 years warranty


## Ref. B1070

Recessed circularLED downlight, outer diameter 116mm, cutout diameter Ø110mm. In white color and aluminum housing, with DARK ENERGY driver without flicker and with EMC filter.5 years warranty \*\* 5 years warranty \*\* 6W6W230V120°IP20



## Product data

Hue	Cool white, Neutral white, Warm white
Kelvin (K)	3000, 6000, 4000
Lumens (Lm)	450
Efficiency (Lm/w)	75
CRI	80-85
Beam angle (°)	120
UGR	No
LED Type	SMD 2835
Dimmable	Yes, by replacing the driver
Nominal Voltage (V)	230
Power factor (cosφ)	0,5
Sensor	No
Orientable	No
Dimensions (mm) Lxlxh	Ø116x15
Material	Aluminum
Diffuser material	Polycarbonate
Use Outdoor	No
IP	IP20







Temperature range Frequency of use	-20°C ∼ +40°C Normal
Lifetime (h)	25000
Energy efficiency class	A+ (2021)
Certificates	CE, ROHS
Warranty	5 years
Cutting dimensions (mm)	Ø110
Mounting	Recessed

-						
D	ra	di	ICT.	var	12	nte
	ıu	uu		vaii	II CIII	IILO

Floudet variants		
Reference	Attributes	
B1070-BC	Colour temperature - Warm White	
B1070-BF	Colour temperature - Cool White	
B1070-BN	Colour temperature - Neutral White	