

Edge-lit LED light BAR 50cm 15W 24V-DC linkable for light box backlighting


Ref. B1425

Rigid LED bar for backlighting of light boxes and double-sided signs. Its lateral installation, together with its 15° x 45° asymmetrical optics, allows an intense, homogeneous and shadow-free illumination in light boxes and double-sided illuminated signs. They are also commonly used as an economical option to create indoor and outdoor wall washers. CREE XTE 3W CHIP. Available in cool white 6000K and warm white 3000K. 15W 50cm 24V Optics 15x45°. 6000K and 3000K IP65 535 XTE




Product data

Hue	Cool white
Kelvin (K)	6000
Efficiency (Lm/w)	100
CRI	80-85
Beam angle (°)	45x15 Asymmetric
UGR	No
LED Type	SMD 3535
Dimmable	Yes
Nominal Voltage (V)	24V-DC
Dimensions (mm) LxIxh	495x26x15
Material	Aluminum
Diffuser material	Plastic
Use Outdoor	Yes
IP	IP65
Temperature range	-20°C ~ +45°C
Frequency of use	Intensive
Lifetime (h)	25000
Energy efficiency class	A+ (2021)



Certificates	CE, ROHS
Adhesive	No

Product variants

Reference	Attributes	
B1425BF	Colour temperature - Cool White	
B1425BC	Colour temperature - Warm White	