



Downlight LED CCT - 40W - IP44 - Cut Ø 205-220mm

Ref. B8590-CCT

Recessed LED downlight of 40W power made of aluminum. It incorporates CCT system that, by means of a selector, allows to choose the color temperature between warm white (3000K), neutral white (4000K) and cold white (6000K). It includes LIFUD driver and has IP44 degree of protection, which makes it suitable for use in wet environments, not directly exposed to liquids. Its installation is very simple and can be used for both domestic and commercial purposes.



Product data

Hue	CCT
Kelvin (K)	3000, 6000, 4000
Lumens (Lm)	5000
CRI	80-85
Beam angle (°)	100
LED Type	SMD 2835
Dimmable	Yes, by replacing the driver
Power (W)	40
Nominal Voltage (V)	220 - 240 V/AC
Frequency (Hz)	50 - 60
Power factor (cosφ)	0,9
Driver	LIFUD
Sensor	No
Orientable	No
Dimensions (mm) LxIhx	Ø230x39
Material	Aluminium
Diffuser material	Polycarbonate
Use Outdoor	No



LED Downlights

IP	IP44
Temperature range	-20°C ~ +40°C
Frequency of use	Normal
Lifetime (h)	25000
Energy efficiency class	A+ (2021)
Certificates	CE, ROHS
Warranty	According to legal guarantee: 2 years
Cutting dimensions (mm)	Ø205-220
Mounting	Recessed