







LED Bulb R7S Fumagalli 78mm 4W 400Lm 100-240V

Ref. H7.LED.R7S

R7S linear LED bulb of 4W power and 400 lumens of luminous flux, with an efficiency of 100Lm/W thanks to its high performance SMD3014 LED chips. It supports a wide voltage range (100-240V) to protect the driver from voltage drops and spikes, frequent in outdoor installations. Its working temperature range -30°C to 80°C allows its use in the most demanding environments. With IP44 protection, it is suitable for outdoor use in sealed lamps. With the guarantee of the FUMAGALLI brand.Ø22x78mm4W100-240V400LmIP44



Product data

| Hue | Neutral white |
|-----------------------|---------------|
| Kelvin (K) | 4000 |
| Lumens (Lm) | 400 |
| Efficiency (Lm/w) | 100 |
| CRI | 80-85 |
| Beam angle (°) | 360 |
| LED Type | SMD 3014 |
| Dimmable | No |
| Equivalence (W) | 50 |
| Power (W) | 4 |
| Nominal Voltage (V) | 230 |
| Frequency (Hz) | 50 - 60 |
| Power factor (cosφ) | 0.5 |
| Driver | Internal |
| Socket | R7S |
| Dimensions (mm) Lxlxh | Ø22x78 |
| Material | Plastic |
| Diffuser material | Polycarbonate |





| Use Outdoor IP | Yes_ IP44 |
|-------------------------|---------------------------------------|
| Temperature range | -30°C ~ +80°C |
| Frequency of use | Normal |
| Lifetime (h) | 25000 |
| Energy efficiency class | A+ (2021) |
| Certificates | CE, ROHS |
| Warranty | According to legal guarantee: 2 years |

Product variants

| Reference | Attributes | |
|----------------|------------------------------------|----------------|
| | | 4W RYS |
| H7.LED.R7S.4K | Colour temperature - Neutral White | |
| | | 3W RYS G |
| H7.LED.R7S.CCT | Colour temperature - CCT | |