


FUMAGALLI CECI 160 3L GX53 10W LED recessed floor spotlight

Ref. 3F3.000.000.AXD1K



Datos del producto

Kelvin (K) 4000 Lumens (Lm) 1200 Efficiency (Lm/w) 120 CRI 80-85 LED Type SMD 2835 Dimmable No Power (W) 10 Nominal Voltage (V) 230 Frequency (Hz) 50 - 60 Power factor (cosφ) 0.5 Socket GX53 Orientable No Dimensions (mm) Lxlxh Ø160x111 Material Resin Diffuser material Polycarbonate Use Outdoor Yes IP 1P67	Hue	Neutral white
Efficiency (Lm/w) 120 CRI 80-85 LED Type SMD 2835 Dimmable No Power (W) 10 Nominal Voltage (V) 230 Frequency (Hz) 50 - 60 Power factor (cosφ) 0.5 Socket GX53 Orientable No Dimensions (mm) Lxlxh Ø160x111 Material Resin Diffuser material Polycarbonate Use Outdoor Yes	Kelvin (K)	4000
CRI 80-85 LED Type SMD 2835 Dimmable No Power (W) 10 Nominal Voltage (V) 230 Frequency (Hz) 50 - 60 Power factor (cosφ) 0.5 Socket GX53 Orientable No Dimensions (mm) Lxlxh Ø160x111 Material Resin Diffuser material Polycarbonate Use Outdoor Yes	Lumens (Lm)	1200
LED Type SMD 2835 Dimmable No Power (W) 10 Nominal Voltage (V) 230 Frequency (Hz) 50 - 60 Power factor (cosφ) 0.5 Socket GX53 Orientable No Dimensions (mm) Lxlxh Ø160x111 Material Resin Diffuser material Polycarbonate Use Outdoor Yes	Efficiency (Lm/w)	120
Dimmable No Power (W) 10 Nominal Voltage (V) 230 Frequency (Hz) 50 - 60 Power factor (cosφ) 0.5 Socket GX53 Orientable No Dimensions (mm) Lxlxh Ø160x111 Material Resin Diffuser material Polycarbonate Use Outdoor Yes	CRI	80-85
Power (W) 10 Nominal Voltage (V) 230 Frequency (Hz) 50 - 60 Power factor (cosφ) 0.5 Socket GX53 Orientable No Dimensions (mm) Lxlxh Ø160x111 Material Resin Diffuser material Polycarbonate Use Outdoor Yes	LED Type	SMD 2835
Nominal Voltage (V) 230 Frequency (Hz) 50 - 60 Power factor (cosφ) 0.5 Socket GX53 Orientable No Dimensions (mm) Lxlxh Ø160x111 Material Resin Diffuser material Polycarbonate Use Outdoor Yes	Dimmable	No
Frequency (Hz) 50 - 60 Power factor (cosφ) 0.5 Socket GX53 Orientable No Dimensions (mm) Lxlxh Ø160x111 Material Resin Diffuser material Polycarbonate Use Outdoor Yes	Power (W)	10
Power factor (cosφ) 0.5 SocketGX53OrientableNoDimensions (mm) LxlxhØ160x111MaterialResinDiffuser materialPolycarbonateUse OutdoorYes	Nominal Voltage (V)	230
SocketGX53OrientableNoDimensions (mm) LxlxhØ160x111MaterialResinDiffuser materialPolycarbonateUse OutdoorYes	Frequency (Hz)	50 - 60
OrientableNoDimensions (mm) LxlxhØ160x111MaterialResinDiffuser materialPolycarbonateUse OutdoorYes	Power factor (cosφ)	0.5
Dimensions (mm) LxlxhØ160x111MaterialResinDiffuser materialPolycarbonateUse OutdoorYes	Socket	GX53
MaterialResinDiffuser materialPolycarbonateUse OutdoorYes	Orientable	No
Diffuser material Polycarbonate Use Outdoor Yes	Dimensions (mm) Lxlxh	Ø160x111
Use Outdoor Yes	Material	Resin
	Diffuser material	Polycarbonate
IP IP67	Use Outdoor	Yes
	IP	IP67







Temperature range	-20°C ~ +40°C
Frequency of use	Normal
Lifetime (h)	25000
Energy efficiency class	A+ (2021)
Certificates	CE, ROHS
Warranty	According to legal guarantee: 2 years
Cutting dimensions (mm)	Ø147x111
Mounting	Recessed