

## LED panel slim 120X30 cm - Driver Philips - 44W - UGR19

### Ref. B5236

The 44W PHILIPS recessed LED panel with driver features a sleek, ultra-slim design and state-of-the-art technology that allows it to provide powerful, uniform illumination in 3 shades: warm white (3000K), neutral white (4000K) and cool white (6000K). It incorporates a micro-prismatic diffuser that ensures glare-free illumination (UGR<19), ideal for offices, conference rooms, schools or hospitals. Thanks to its high color rendering index (CRI>80) it reproduces colors very similar to natural light. The panel can be mounted in false ceilings (120x30cm removable ceiling tiles) or recessed directly into plasterboard using a recessing frame (not included).






### Product data

Hue	Cool white, Neutral white, Warm white
Kelvin (K)	3000, 6000, 4000
Lumens (Lm)	2900
CRI	80-85
UGR	UGR19
LED Type	SMD 2835
Power (W)	44
Nominal Voltage (V)	220 - 240 V/AC
Frequency (Hz)	50 - 60
Driver	Philips
Sensor	No
Orientable	No
Dimensions (mm) Lxlxh	1200 x 300 x 6
Diffuser material	Polycarbonate
Use Outdoor	No
IP	IP20
Frequency of use	Intensive
Lifetime (h)	25000



Energy efficiency class	A+ (2021)
Certificates	CE, ROHS
Warranty	According to legal guarantee: 2 years
Mounting	Recessed
LED Panel dimensions	120x30

## Product variants

Reference	Attributes	
B5236-BN	Colour temperature - Neutral White	 <p>44W URC&lt;19 95 lm/W</p>
B5236-BC	Colour temperature - Warm White	 <p>44W URC&lt;19 95 lm/W</p>
B5236-BF	Colour temperature - Cool white 6000K	 <p>44W URC&lt;19 95 lm/W</p>