

Slim surface LED panel 120X30 cm - Driver Philips - 44W - UGR19 - With mounting KIT

Ref. B4290

The PHILIPS 44W surface mounted LED panel with driver features a sleek, ultra-slim design and state-of-the-art technology that allows it to provide powerful, uniform illumination in 3 shades: warm white (2800K), neutral white (4000K) and cool white (6000K). It incorporates a micro-prismatic diffuser that ensures glare-free illumination (UGR<19), ideal for offices, conference rooms, schools or hospitals. Thanks to its high color rendering index (CRI>80) it reproduces colors very similar to natural light. Includes surface mounting kit with all accessories for easy and fast installation.





Product data

Hue	Cool white, Neutral white, Warm white
Kelvin (K)	3000, 6000, 4000
Lumens (Lm)	2900
CRI	80-85
UGR	UGR19
LED Type	SMD 2835
Dimmable	Yes, by replacing the driver
Power (W)	44
Nominal Voltage (V)	220 - 240 V/AC
Frequency (Hz)	50 - 60
Driver	Philips
Sensor	No
Orientable	No
Diffuser material	Polycarbonate
Use Outdoor	No
IP	IP20
Frequency of use	Intensive
Lifetime (h)	25000

Energy efficiency class	A+ (2021)
Certificates	CE, ROHS
Warranty	According to legal guarantee: 2 years
Mounting	Surface
LED Panel dimensions	120x30

Product variants

Reference	Attributes	
B4290-BC	Colour temperature - Warm white 3000K	
B4290-BN	Colour temperature - Neutral white 4000K	
B4290-BF	Colour temperature - Cool white 6000K	