







TRIAC dimmable driver constant current 43-70V 20W 250mA

Ref. PE296R7025

Dimmable Triac constant current driver, 43-70V/DC, 250ma, 20W.Triac dimmable constant current, TUV certified, specially designed for TRIAC dimming of LED luminaires. NO Flicker, no flicker. SCP/OCP/OVP/OVP/OTP protections. Intelligent PFC dimming, dimming range 2/100%.Warranty 2 years.



Datos del producto

Power (W)2Nominal Voltage (V)180-240V-AFrequency (Hz)50 - 6SensorNDimensions (mm) Lxlxh104x39x2MaterialPlastiUse OutdoorNIPIP2Temperature range-20 ~ +65°Frequency of useIntensivLifetime (h)2500
Frequency (Hz)50 - 6SensorNDimensions (mm) Lxlxh104x39x2MaterialPlastiUse OutdoorNIPIP2Temperature range-20 ~ +65°Frequency of useIntensiv
SensorNDimensions (mm) Lxlxh104x39x2MaterialPlastiUse OutdoorNIPIP2Temperature range-20 ~ +65°Frequency of useIntensiv
Dimensions (mm) Lxlxh104x39x2MaterialPlastiUse OutdoorNIPIP2Temperature range-20 ~ +65°Frequency of useIntensiv
MaterialPlastiUse OutdoorNIPIP2Temperature range-20 ~ +65°Frequency of useIntensiv
Use OutdoorNIPIP2Temperature range-20 ~ +65°Frequency of useIntensiv
IP IP2 Temperature range -20 ~ +65° Frequency of use Intensiv
Temperature range-20 ~ +65°Frequency of useIntensiv
Frequency of use Intensiv
Lifetime (h) 2500
Energy efficiency class A+ (2021
Certificates CE, ROH
Warranty According to legal guarantee: 2 year
Connectivity By wirin
Control system TRIA
Output voltage (V) 43-70V-D
Number of channels



