

100lm/W
Alta eficiencia
High efficiency
Haute efficacité



4W



Recessed circular LED downlight 4W Cut Ø77mm

Ref. B1240

4W circular recessed LED plate, outer diameter 98mm, cutting diameter Ø77mm. In white color and polycarbonate housing. The DOB offers a luminaire that does not generate any electromagnetic noise, unlike lighting powered by switched sources. Lighting solution that combines excellent efficiency with a compact design. 4W230V120°IP20



Driver de fuente
de luz integrado

Ángulo de 120°
Luz brillante y amplia





Product data

Hue	Cool white, Neutral white, Warm white
Kelvin (K)	3000, 6000, 4000
Efficiency (Lm/w)	100
CRI	80-85
LED Type	SMD 2835
Dimmable	No
Nominal Voltage (V)	230
Orientable	No
Dimensions (mm) LxLxh	98x98x25.5
Diffuser material	Polycarbonate
Use Outdoor	No
IP	IP20
Temperature range	-20°C ~ +40°C
Frequency of use	Normal
Lifetime (h)	25000
Energy efficiency class	A+ (2021)
Certificates	CE, ROHS
Warranty	According to legal guarantee: 2 years



Cutting dimensions (mm)	Ø77-82
Mounting	Recessed

Product variants

Reference	Attributes	
B1240-B-4W-BF	Colour temperature - Cool White	
B1240-B-4W-BN	Colour temperature - Neutral White	
B1240-B-4W-BC	Colour temperature - Warm White	