







CCT "Livia 160" FUMAGALLI outdoor ceiling light - 7W - GX53 - IP55


Ref. 3A9.000.000

Outdoor ceilingfixture of the Italian firm FUMAGALLI, of great design and quality. It is made of resin resistant to shock, corrosion and degradation by UV rays. Due to its IP55 degree of protection it is suitable for outdoor use. It incorporates a frosted diffuser and includes a 7W GX53 LED bulb, with CCT system, which allows you to adjust the color temperature between warm white, neutral white and cool white.

		GXS3 Ø100 - OCT SETTABLE	
	PECS	POWER	7 W
	2 0	LUMINOUS FLUX	800 lm
16 W 1200 Im No.		525 A 500KET	8053
200 20		SEFICIENCY	114 Lm/W
de m		VOLTAGE	100-248 V
11111	wanness!	FREQUENCY	50/90 Hz
100	8 8 8 8 8 8 E E E E E E E	CURRENT	34 mA
CETSETTRALE	One-more	POWER FACTOR	0.8
200 K 100 F 200 K		COLOR PENDERSYS INSEX RA	> 80
		SOOM	+6
SILICONE PROTECTION	The same of the same	BEAM ANGLE	120°
	CE	WARH UP TIME	0.6
	CB	SWITCHING CYCLE	× 30,000
	CB	LIFETIME	25.000 h
	LVD EMC ERP	HELVIN SETTABLE	3000 K 74000 K74503 K
AT ASSESSMENT	EAC CHO 1900	REF. CODE	H2.LE0.053.CCT
UNDOOR & OUTDOOR USE -IN-IN-YE MADEEN VECTOR SHORE RESISTANT	IFCEE TO THE STATE OF THE STATE	COMPLESION	7W • 75W 800 Ln

Product data

Hue	CCT
Kelvin (K)	3000, 4000, 6500
Lumens (Lm)	800
CRI	80-85
Dimmable	No
Power (W)	7
Nominal Voltage (V)	100 - 240 V/AC
Frequency (Hz)	50 - 60
Sensor	No
Socket	GX53
Orientable	No
Dimensions (mm) Lxlxh	Ø160x100x145
Material	Resin
Use Outdoor	Yes
IP	IP55
Temperature range	-20°C ~ +40°C
Frequency of use	Intensive
Certificates	CE, ROHS





Warranty According to legal guarantee: 2 years
Mounting Surface

Product variants		
Reference	Attributes	7W 0150
		7W Ø150 ©
3A9.000.000.AXC1K	Colour - Black	fumāgalti"
		7W 9150 (#3)
3A9.000.000.WXC1K	Colour - White	fumāgalii
		7W 6350 (m)
3A9.000.000.LXC1K	Colour - Grey	fumāgalii: