



Outdoor LED Floodlight 30W 2806LM IP65

Ref. B1882-2

30WLED outdoor flood light with IP65 protection degree. With high quality reflector that offers a bright illumination, without shadows and with an opening angle of the light beam of 120 degrees. With metal housing finished in black color. A choice of warm 3000°K shades, with a luminous intensity of 2594lm, and a cool 6000°K shade, with a total of 2806lm. Compact design, with dimensions of 175x130mm. SMD 2835 LED chip. 230V. CRI>80. Optimal heat dissipation. LED projectors perfect for installation as outdoor or indoor lighting in gardens, garages, warehouses, courtyards, workshops, etc.. Bracket included to orient the LED projector to the desired direction.




Product data

Hue	Cool white, Warm white
Kelvin (K)	3000, 6000
Lumens (Lm)	2594, 2806
Efficiency (Lm/w)	86
CRI	80-85
Beam angle (°)	120
UGR	No
LED Type	SMD 2835
Dimmable	No
Power (W)	30
Nominal Voltage (V)	220 - 240 V/AC
Frequency (Hz)	50 - 60
Power factor (cosφ)	0.6
Driver	Internal
Sensor	No
Orientable	Yes
Dimensions (mm) LxH	154x106x30
Material	Aluminium



Diffuser material	Glass
Use Outdoor	Yes
IP	IP65
Temperature range	-20°C ~ +50°C
Frequency of use	Normal
Lifetime (h)	25000
Certificates	CE, ROHS
Warranty	According to legal guarantee: 2 years
Mounting	Surface

Product variants

Reference	Attributes	
B1882-2-BF	Colour temperature - Cool White	
B1882-2-BC	Colour temperature - Warm White	