

## LED Panel 60X60cm with recessed KIT 44W UGR19 Driver Philips

### Ref. B4295-UGR19

60x60cm recessed LED panel with 44W extra flat SMD2835 Philips Driver, UGR19. The mounting kit includes all accessories for quick and easy installation of recessed. Kit consists of panel, 4 fastening clips and frame. Low glare index (UGR19). With high performance Philips driver, EMC filter. Warm white 3000°K, 2822lm. Neutral white 4000°K, 3432lm. Cool white 6000°K, 3822lm. High luminous efficiency of 87lm/W. The LED panel can be mounted on Armstrong ceiling (60x60 removable false ceiling panels), recessed directly to plasterboard. Possibility of dimming by TRIAC or DALI.



### Product data



Hue	Cool white, Neutral white, Warm white
Kelvin (K)	3000, 6000, 4000
Lumens (Lm)	3822, Empotrable, 3822
Efficiency (Lm/w)	87
CRI	80-85
LED Type	SMD 2835
Dimmable	Optional, replacing the driver
Nominal Voltage (V)	230V
Frequency (Hz)	50 - 60
Driver	External
Sensor	No
Orientable	No
Dimensions (mm) LxIxh	595x595x9,5
Diffuser material	Polycarbonate
Use Outdoor	No
IP	IP20
Temperature range	-0°C ~ +30°C
Frequency of use	Intensive

↔ Driver Philips 123x43mm  
⊥ Grosor: 8mm



Lifetime (h)	25000
Energy efficiency class	A+ (2021)
Certificates	CE, ROHS
Warranty	3 years
Cutting dimensions (mm)	600x600
Mounting	Recessed
LED Panel dimensions	60x60

## Product variants

Reference	Attributes	
B4295-UGR19-BF	Colour temperature - Cool White	
B4295-UGR19-BC	Colour temperature - Warm White	
B4295-UGR19-BN	Colour temperature - Neutral White	