








Recessed LED Panel 1200X600mm Slim 72W PHILIPS DRIVER UGR19 with mounting K IT

Ref. B4296

Slim recessed LED panel 120x60cm and 72W power of the PHILIPS brand, ultra thin with avant-garde aesthetics, suitable for all types of professional / home projects. It integrates perfectly into any surface. Placement options: Recessed in Armstrong ceiling (removable ceiling tiles 120x60cm), or by means of anchoring staples directly embedded in plasterboard false ceilings, or suspended by means of the ceiling hanging kit. Includes a 2 CERTA DRIVE PHILIPS. Accessories are sold separately.Includes recessed kit, frame, staples, screws (1200x600mm), with all accessories for quick and easy installation.- x2 Driver: CertaDrive PHILIPS- 230V- 4000LM- 120°- 1200x600mm- IP20- UGR19



Product data

Hue	Cool white, Neutral white, Warm white
Kelvin (K)	3000, 6000, 4000
Lumens (Lm)	6100
Efficiency (Lm/w)	85
CRI	80-85
Beam angle (°)	160°
LED Type	SMD 2835
Power (W)	72
Nominal Voltage (V)	230V
Frequency (Hz)	50 - 60
Driver	External
Sensor	No
Orientable	No
Dimensions (mm) Lxlxh	1200x600mm
Diffuser material	Polycarbonate
Use Outdoor	No
Frequency of use	Intensive
Energy efficiency class	A+ (2021)



Certificates	CE, ROHS
Warranty	3 years
Mounting	Recessed
LED Panel dimensions	120x60

Product variants		
Reference	Attributes	
B4296-BC	Colour temperature - Warm white 3000K	72W UIG-19 29 PHELIPS
B4296-BN	Colour temperature - Neutral white 4000K	72W WO UIG-19 WO UIG-19
B4296-BF	Colour temperature - Cool white 6000K	72W © UBG-19 PHELIPS PHELIPS