




Recessed LED Panel - 60X60cm - TRIAC dimmable - 44W - UGR19

Ref. K5235-TRIAC

Ultra-thin recessed LED panel with cutting-edge technology that enables it to provide powerful and even illumination. It's a high efficiency luminaire with a power of 44W and a luminous flux of 3800 lumens. It incorporates a TRIAC dimming driver, providing the possibility to adjust the light intensity. Thanks to its low glare index, UGR19, this panel provides great visual comfort. It's available in three color temperatures: warm white (3000K), neutral white (4000K) and cool white (6000K).





Product data

Hue	Cool white, Neutral white, Warm white
Kelvin (K)	3000, 6000, 4000
Lumens (Lm)	3800
CRI	80-85
LED Type	SMD 2835
Dimmable	Yes
Power (W)	44
Nominal Voltage (V)	220-240 V
Frequency (Hz)	50 - 60
Sensor	No
Orientable	No
Dimensions (mm) LxLxh	600 x 600 x 6
Diffuser material	Polycarbonate
Use Outdoor	No
IP	IP20
Temperature range	-0°C ~ +30°C
Frequency of use	Intensive
Lifetime (h)	25000



Certificates	CE, ROHS
Warranty	3 years
Cutting dimensions (mm)	600x600mm
Mounting	Recessed
LED Panel dimensions	60x60

Product variants

Reference	Attributes	
K5235-TRIAC-BC	Colour temperature - Warm White	
K5235-TRIAC-BN	Colour temperature - Neutral White	
K5235-TRIAC-BF	Colour temperature - Cool White	