



INPUT		LED Driver (LED 控制装置)		DALI	
AC-L		Model: LF-GSD040YG		Preparation for input and output	
AC-N		Input: 220-240V ~ 50/60Hz Max 0.3A		73mm	
PUSH		U out: 59Vrms PF: >0.9C Prated: 44.1W(Max)			
DA1		For 2-Channel LED Driver			
DA2		For Australia and New Zealand, the marking label with			
0.75-1.5		Output current and setting table			
		1	2	3	4
1050mA		OFF	OFF	OFF	OFF
1000mA		OFF	OFF	OFF	ON
950mA		OFF	OFF	ON	OFF
900mA		OFF	OFF	ON	ON
850mA		OFF	ON	OFF	OFF
800mA		OFF	ON	OFF	ON
750mA		OFF	ON	ON	OFF
700mA		OFF	ON	ON	ON
650mA		ON	OFF	OFF	OFF
600mA		ON	OFF	OFF	ON
550mA		ON	OFF	ON	OFF

Driver LIFUD DALI-2 DT8



LIFUD Driver a corrente costante dimmerabile DALI e PUSH 550-1050mA 20-42 VDC 40W CCT2000-7000K

Ref. LF-GSD040YG

Il driver LIFUD LF-GSD040YG è un driver LED a corrente costante da 40W con funzioni di dimmerazione DALI e dimmerabili. La tensione di ingresso è di 220-240V e l'uscita è di 20-42V. La corrente di uscita può essere regolata da 550mA a 1050mA tramite interruttore DIP, con incrementi di 50mA.

Dati del prodotto

Kelvin (K)	2000-7000K
Dimmerabile	0%-100% (0.1%)
Tensione nominale (V)	220-240V
Frequenza (Hz)	50 - 60
Dimensioni (mm) LxIxh	80.8x126.2x31.2mm
Materiale	Plastica
IP	IP20
Intervallo di temperatura	-20°C ~ +40°C
Potenza massima (W)	40w
Tensione di uscita (V)	20-42V
Corrente di uscita mA	550-1050mA

Driver LIFUD DALI-2 DT8

